

TECHNICAL SPECIFICATIONS

FUENTE I is equipped with a dedicated point gas heater. The furnace is characterized by a decorative cover made of sheet metal, which protects against direct contact with fire.

The heater emits **flame** which **does not besmoke or leave dirt** on the glass thanks to which the vision of fire is always perfect. The range of power can be regulated within **7 levels of intensity**. The change of settings as well as turning off the heater is possible at any time. Automatic and intuitive control panel is hidden in the heater housing. Those who value comfort can choose additional remote operation using remote control.

Gas heaters **do not emit smog and are environmentally friendly**. They work with gas from propane-butane cylinder or pure propane.

Due to the fact that the heater may be exposed to different weather conditions **only rust-resistant and protected with a varnish coating materials were used for its production**. The burner and all the elements in direct contact with the fire are made of a boiler steel (resistant to widespread temperature fluctuations) and are covered with anti-corrosion layer (galvanised) on which a special high-temperature fireplace paint was applied. The modern system of gas control has been equipped with a **thermocouple** which is supposed to cut off the gas flow in case of flame disappearance.

2 years
WARRANTY

7 levels
flame
intensity



Type of fuel	A mixture of gases propane butane, propane gas
Nominal power [kW]	4,3
Minimum power [kW]	0,9
Maximum gas consumption [kg/h]	0,28
Minimum gas consumption [kg/h]	0,06
Material	Boiler steel P265GH according to EN 10028-2
Weight [kg]	19
Dimensions width x height x depth [mm]	600 x 1270 x 600
Control valve	Anstoss TESCO1
Control	Control panel / Remote control (optional)
Power supply	Batteries / Power adapter (option)
Warranty	2 years
Color versions	czarny ●

