

DECLARATION OF PERFORMANCE

DoP/AL17R.H-D/001

1. Unique identification code of the product-type	AL19S.H
2. Intended use or uses	space heating in residential buildings
3. Manufacturer	STALKO Sp. Z o.o. , sp. komandytowa ul. Marii Rodziewiczówny 1/193 04-187 Warszawa (+48) 48 377 99 99 info@hitze.pl hitze.pl
4. Authorised representative	-
5. System of assessment and verification of constancy of performance	System 3
6. Harmonised standard	EN 16510-2-1:2022
Notified Body	NB1452 Instytut Energetyki ul. Mory 8 01-330 Warszawa
7. Declared performance	
– Minimum distance to combustible materials – bottom (d_B)	non-combustible floor
– Minimum distance to combustible materials – floor in front (d_F)	1500 mm
– Minimum distance to combustible materials – ceiling (d_C)	≥ 750 mm
– Minimum distance to combustible materials – rear (d_R)	200 mm
– Minimum distance to combustible materials – side/side with glass (d_S)	200 mm
– Minimum distance to combustible materials – lateral radiation (d_L)	1500 mm
– Minimum distance to combustible materials – e.g. furniture (d_P)	2000 mm
– Carbon monoxide (CO) emission	1200 mg/Nm ³ (13 % O ₂)
– Nitrogen oxides (NOx) emission	90 mg/Nm ³ (13 % O ₂)
– Organic gaseous compounds (OGC) emission	43 mg/Nm ³ (13 % O ₂)
– Particulate matter (PM) emission	29 mg/Nm ³ (13 % O ₂)
– Flue gas outlet temperature	376°C
– Minimum chimney draught	12 Pa
– Mass flow rate of dry combustion products	12,7 g/s
– Nominal heat output	17 kW
– Water heat output	NPD kW
– Efficiency at nominal heat output	81 %
8. Test report number	CUE.4032.003.2.2024.2026.AoP.033

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Radom, 16.06.2026

Signed for and on behalf of the manufacturer by
President of the Management Board

Michał Ziomek